ASEC



VIBRATION MOUNTS AVACCFS

SKU: AVACCFS

ASEC Kunststoffen BV

Marketing 17, 6921 RE Duiven, The Netherlands

T: +31 316 84 44 01 | info@asec.nl

Categories: Bell mounts

Mounts which allow a high level of insulation, especially used on generators, engines and systems with an operating frequency at around 25 Hz (1500 rpm). The AVACCFS are designed with a fail-safe function making them an ideal solution for applications where safety is paramount. Axial stresses are perfectly absorbed and side deflections limited to guarantee a good stability. The AVACCFS can accommodate loads between 12 kg to 1950 kg per mount. Our bell mounts can withstand up to 2g of shock forces or 5g occasional shock forces,
with regards to the load, without permanent deformation or failing.

Optional orderring stainless steel version. Compatible with Height adjuster AVCHA

The information in this datasheet is provided for general purposes only and not meant to be a specific recommendation for any individual application. All values were determined under laboratory conditions. ASEC Products is not directly neither indirectly responsible for any claim resulting from the use of any information provided in this datasheet.
ASEC Products 2022 ©.

ASEC

The information in this datasheet is provided for general purposes only and not meant to be a specific recommendation for any individual application. All values were determined under laboratory conditions. ASEC Products is not directly neither indirectly responsible for any claim resulting from the use of any information provided in this datasheet.
ASEC Products 2022 ©.