ASEC



VIBRATION MOUNTS AVCFQ

SKU: AVCFQ

ASEC Kunststoffen BV

Marketing 17, 6921 RE Duiven, The Netherlands

T: +31 316 84 44 01 | info@asec.nl

Categories: Bell mounts

Mounts which allow a high level of insulation, especially used on generators, engines and systems with an operating frequency at around 25 Hz (1500 rpm). Axial stresses are perfectly absorbed and side deflections are limited to guarantee a good stability. The AVCF mounts are fully bonded, have a threaded insert to allow an easy assembling and can accommodate loads between 150 kg to 2014 kg per mount.

Optional orderring stainless steel version. Compatible with Height adjuster AVAHA. Compatible with Height adjuster AVBHA.

The information in this datasheet is provided for general purposes only and not meant to be a specific recommendation for any individual application. All values were determined under laboratory conditions. ASEC Products is not directly neither indirectly responsible for any claim resulting from the use of any information provided in this datasheet.
ASEC Products 2022 ©.

ASEC

The information in this datasheet is provided for general purposes only and not meant to be a specific recommendation for any individual application. All values were determined under laboratory conditions. ASEC Products is not directly neither indirectly responsible for any claim resulting from the use of any information provided in this datasheet.
ASEC Products 2022 ©.