ASEC



FRICTION MATERIAL AB-3080

SKU: AB3080

ASEC Kunststoffen BV

Marketing 17, 6921 RE Duiven, The Netherlands

T: +31 316 84 44 01 | info@asec.nl

Categories: Organic moulded

Asbestos-free, pressed composite friction material containing metallic components. AB3080 is based on phenolic resins with NBR rubber bonding system, containing short fibers, organic components, friction modifiers, metallic particles and fillers. AB3080 is suitable for dry and oil-immersed applications. AB3080 is not abrasive to the counter face material and is silence in operation, It is resistant to high pressures and has low wear rate even at high temperatures.

Resistance to oil. Resistance to high pressure. Low wear rate even at high temperatures.

The information in this datasheet is provided for general purposes only and not meant to be a specific recommendation for any individual application. All values were determined under laboratory conditions. ASEC Products is not directly neither indirectly responsible for any claim resulting from the use of any information provided in this datasheet.
ASEC Products 2022 ©.

ASEC

The information in this datasheet is provided for general purposes only and not meant to be a specific recommendation for any individual application. All values were determined under laboratory conditions. ASEC Products is not directly neither indirectly responsible for any claim resulting from the use of any information provided in this datasheet.
ASEC Products 2022 ©.