ASEC



FRICTION MATERIAL AB-3160

SKU: AB3160

ASEC Kunststoffen BV

Marketing 17, 6921 RE Duiven, The Netherlands

T: +31 316 84 44 01 | info@asec.nl

Categories: Organic moulded

Asbestos-free, pressed composite friction material containing metallic components. AB3160 is based on phenolic resins with NBR rubber bonding system, containing short fibers, organic components, friction modifiers, metallic particles, and fillers. AB3160 is suitable for dry and oil immersed applications. AB3160 is not abrasive to the counter face material and is silence in operation. AB3160 is resistant to high pressure. It has low wear rate even at high temperatures.

Resistant to high pressure. Low wear rate. For dry and oil immersed applications. Non abrasive to counter face material. Silence in operation.

The information in this datasheet is provided for general purposes only and not meant to be a specific recommendation for any individual application. All values were determined under laboratory conditions. ASEC Products is not directly neither indirectly responsible for any claim resulting from the use of any information provided in this datasheet.
ASEC Products 2022 ©.

ASEC

The information in this datasheet is provided for general purposes only and not meant to be a specific recommendation for any individual application. All values were determined under laboratory conditions. ASEC Products is not directly neither indirectly responsible for any claim resulting from the use of any information provided in this datasheet.
ASEC Products 2022 ©.