ASEC



INSULATION MATERIAL AI-PFCC24

SKU: AIPFCC24

ASEC Kunststoffen BV

Marketing 17, 6921 RE Duiven, The Netherlands

T: +31 316 84 44 01 | info@asec.nl

Categories: Cotton fabric phenol

AI PF CC 24 for mechanical applications. Impact-resistant, noise-reducing, wear-resistant material. Well suited as a low-friction material. High wear resistance in aggressive and dust-filled environments. Can be lubricated with water, oil or grease. Examples of applications are ball-bearing cages for spindle bearing and guide rings for hydraulic cylinders. Can be used, in particular, for mechanical applications where fine tolerances and smooth surface finish are required.

Suitable for mechanical applications where fine tolerances and surface coarseness are required. Shockproof, noise-reducing and hard-wearing construction material. Weather and saltwater resistant.

The information in this datasheet is provided for general purposes only and not meant to be a specific recommendation for any individual application. All values were determined under laboratory conditions. ASEC Products is not directly neither indirectly responsible for any claim resulting from the use of any information provided in this datasheet.
ASEC Products 2022 ©.

ASEC

The information in this datasheet is provided for general purposes only and not meant to be a specific recommendation for any individual application. All values were determined under laboratory conditions. ASEC Products is not directly neither indirectly responsible for any claim resulting from the use of any information provided in this datasheet.
ASEC Products 2022 ©.