ASEC



SLIDING BEARINGS ASA15TG(F)

SKU: ASA15TG(F)

ASEC Kunststoffen BV

Marketing 17, 6921 RE Duiven, The Netherlands

T: +31 316 84 44 01 | info@asec.nl

Categories: Composite bearings

TriboGlide 15 materials have proven highly successful in offshore applications, including launch systems, tow pins, winches, cranes, anchor-handling equipment, and mooring systems.

The information in this datasheet is provided for general purposes only and not meant to be a specific recommendation for any individual application. All values were determined under laboratory conditions. ASEC Products is not directly neither indirectly responsible for any claim resulting from the use of any information provided in this datasheet.
ASEC Products 2022 ©.

ASEC

Availablity		Value	Unit
Min. inside diameter		12	mm
Max. outside diameter		2300	mm
Length standard		450 / 670 / 950	mm
Sheet size		450x450/670x670/950x950	mm
Sheet thickness		2.5-200	mm
Mechanical properties	Test standard	Value	Unit
Compressive strength		375	MPa
Dynamic load capacity		70	MPa
Thermal properties	Test standard	Value	Unit
Min. working temperature		-40	°C
Max. working temperature		70	°C
Friction properties	Test standard	Value	Unit
Dynamic friction		0.04~0.07	[-]
Max. pv load		0.58	MPa*m/s

The information in this datasheet is provided for general purposes only and not meant to be a specific recommendation for any individual application. All values were determined under laboratory conditions. ASEC Products is not directly neither indirectly responsible for any claim resulting from the use of any information provided in this datasheet.
ASEC Products 2022 ©.