ASEC



SLIDING BEARINGS ASLFG

SKU: ASLFG

ASEC Kunststoffen BV

Marketing 17, 6921 RE Duiven, The Netherlands

T: +31 316 84 44 01 | info@asec.nl

Categories: Plastic bearings

Features

- Recommended Axles: h9. Maintenance free, self-lubricated.
- Use Two bolts to place the bearings on a flat surface.
- Low tolerance requirement for the mounting holds.
- Suitable for rotation, oscillation and sliding motions.
- Easy installation.

Material
Plastic

The design of flange bearings enables the use of high-performance plain bearings in situations where achieving tolerance in the base bore is challenging. Despite requiring minimal base accuracy, this bearing design can still endure high loads. Maintenance-free flange bearings are available in ASGPE and ASJPE materials. These bearings offer excellent self-lubrication and long-term wear resistance, allowing for dry running. ASGPE types are suitable for general-purpose applications, ASJPE types offer low friction coefficients, ASXPE types are resistant to high temperatures, and options compliant with FDA food grade standards are also available.

The information in this datasheet is provided for general purposes only and not meant to be a specific recommendation for any individual application. All values were determined under laboratory conditions. ASEC Products is not directly neither indirectly responsible for any claim resulting from the use of any information provided in this datasheet.
ASEC Products 2022 ©.

ASEC

The information in this datasheet is provided for general purposes only and not meant to be a specific recommendation for any individual application. All values were determined under laboratory conditions. ASEC Products is not directly neither indirectly responsible for any claim resulting from the use of any information provided in this datasheet.
ASEC Products 2022 ©.