ASEC



MILLI SCRATCH TESTER PREMIUM

SKU: MILLI-SCRATCH-TESTER-PREMIUM

ASEC Kunststoffen BV

Marketing 17, 6921 RE Duiven, The Netherlands

T: +31 316 84 44 01 | info@asec.nl

Categories: Tribodesign

Combined a very accurate milli tribometer and milli scratch tester."Smart scratch display"."Smart Scratch report" .

In accordance with Standard JIS 3255. The scratch test method consists of scratching on the surface, with a diamond tip on which is applied a constant or progressive load. As the scratching is done, the sample moves under the video system, to examine the different kind of damage done by the tip and correlate it with the load applied. Pictures can be digitized and positioned precisely loading graphs. This standard method allows for comparison of different coatings, substrates, thickness of coating, preparation of surface and scratch resistance of bulk materials.

The information in this datasheet is provided for general purposes only and not meant to be a specific recommendation for any individual application. All values were determined under laboratory conditions. ASEC Products is not directly neither indirectly responsible for any claim resulting from the use of any information provided in this datasheet.
ASEC Products 2022 ©.

ASEC

The information in this datasheet is provided for general purposes only and not meant to be a specific recommendation for any individual application. All values were determined under laboratory conditions. ASEC Products is not directly neither indirectly responsible for any claim resulting from the use of any information provided in this datasheet.
ASEC Products 2022 ©.